

## BA-M-CP-865-24-G5

BackLED M CP G5 | LED modules for light advertising and backlighting



### Product family features

- LED chain comprising 40 LED modules connected by flexible cables
- Each LED module contains 2 LEDs
- LED module pitch variable between 60 and ~ 200 mm
- Compatible with OSRAM OPTOTRONIC constant voltage drivers / dimmers
- Color consistency in 3 SDCM
- Patented Square Lens technology
- Wide CCT and color options available
- IP66 rating
- Lifetime (L70/B50): 50,000 h (temperature at  $T_c = 70\text{ }^\circ\text{C}$ )
- 5-year warranty @  $T_a = 70\text{ }^\circ\text{C}$

### Product family benefits

- High module efficacy: up to 135 lm/W
- Uniform light pattern design for 60-200 mm lightbox depth
- Backside injection technology for high protection level
- Flammability rating at V0

### Areas of application

- Channel letters
- Signage boxes
- Luminous areas and ceilings



## Product datasheet

### Technical data

#### Electrical data

Nominal voltage	24.0 V
Nominal wattage per chain	24.00 W
Nominal wattage per LED module	0.6 W
Accidental reverse input voltage protection up to	25 V
Input voltage range	23.4...24.9 V
Type of current	DC

#### Photometrical data

Color temperature	6500 K
Color rendering index Ra	80
Light color LED	Cool white
Luminous flux per LED module	80 lm
Luminous efficacy	138 lm/W
Standard deviation of color matching	≤3 sdcM
Luminous flux per chain at Ta 25 °C	3333 lm


#### Light technical data

Beam angle	155 °
------------	-------

#### LED module information

Number of LEDs per module	2
Number of LED modules per chain	40
Minimum operable number of LED modules	1

#### Dimensions & weight



Length	35.5 mm
--------	---------

## Product datasheet

Width	12.2 mm
Height	10.3 mm
Product weight	225.00 g

### Temperatures & operating conditions

Temperature range in operation at Tc point	-25...70 °C
Temperature range at storage	-25...85 °C

### Lifespan

Lifespan	50000 h
----------	---------

### Additional product data

Product remark	Modules perfectly matched to OSRAM OPTOTRONIC LED drivers (see relevant table)/For current photometric data and important safety, installation and application information (see <a href="http://www.osram.com/led-systems">www.osram.com/led-systems</a> )./In view of the complex manufacturing process for light emitting diodes, the typical values given above for the technical LED parameters are merely statistical values that do not necessarily correspond to the actual technical parameters of an individual product; individual products may vary from the typical values
ID of contained light source	LS_SHZ_600816

### Capabilities

Dimmable	Yes
Dimming range	1...100 %

### Certificates & standards

Energy consumption	24 kWh/1000h
Type of protection	IP66
Standards	Acc. to EN 62471:2008/Acc. to IEC 62031/ENEC/CE/UL
Approval marks – approval	CE / cURus / ENEC 25 / UKCA / BIS
Energy efficiency class of the contained light source	E

### Logistical data


Commodity code	940540399000
----------------	--------------

## Product datasheet

### Additional product information

- Installation of LED modules (with power supplies) needs to be made under consideration of all valid regulations and norms.
- Installation by qualified electrician only.
- Please see the relevant application guides and instructions sheets for more detailed safety and mounting information.  
Additional information is available on request.

### Download Data

File
 User instruction BackLED CP G5 User Instruction 20210730

### Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899627765	BA-M-CP-865-24-G5	Shipping carton box 30	355 mm x 255 mm x 240 mm	21.73 dm <sup>3</sup>	7490.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### Accessories Optional

Product description	Accessory name	Accessory code
BA-M-CP-865-24-G5	BA -MP-SM-G5-2M	▶ 4052899629196
BA-M-CP-865-24-G5	BA -CLIP-SM-G5	▶ 4052899629349

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.